

World Class Industries

375 E. Prairie Street Crystal Lake, IL 60014 Phone: 888-SMARTBOX (opt. 1) 888-762-7826 (opt. 1) Fax: 815-479-9975

John Deere[™] Insecticide Drop Tube Instructions – Front Side Mount

Part No. SB020754: bolt-on attachment

Drop tube SB020754 is used for SmartBox[®] system front mount applications on John DeereTM planters equipped with 3 bushel seed boxes.

The SB020754 tube is used on 2005 and newer John DeereTM MaxEmerge[®] XP or Pro-Series[®] XP planters that have a one-piece ductile cast iron shank.

Note: 2004 and earlier John DeereTM $MaxEmerge^{\mathbb{R}}$, $MaxEmerge^{\mathbb{R}}$ 2, $MaxEmerge^{\mathbb{R}}$ Plus planters that have a fabricated steel shank use the weld-on SB020749 drop tube.

- 1. Place the tube down into the indentation on the shank, in front of the opening disks.
- 2. Then attached with the provided bolt and nut to the vertical upright. Tighten to secure the drop tube.

Note: If the tube rubs on the inside of the opening disk, it may be necessary to slightly flatten this section of tube. A minimum tube opening of 3/16" must be maintained.





General Mounting Instructions: Your SmartBox® system requires that a minimum 45 degree angle be maintained at any point along the product discharge path from the meter outlet to the in-furrow drop tube. The drop tube may need to be bent to adjust. The plastic hose should be cut to length to eliminate any unnecessary slack that could cause a flow restriction. Also, if using a seed firmer the drop tube's foot (if applicable) may need to be cut off or bent up if restricting the firmer's travel.



