

World Class Industries

375 E. Prairie St. Crystal Lake, IL 60014 Phone: 888-SMARTBOX (opt. 1) 888-762-7826 (opt. 1) Fax: 815-479-9975

SMARTBOX[®] MOUNTING BRACKET INSTALLATION INSTRUCTIONS John DeereTM Short Front Mount Bracket (fits CCS planters) Bracket Kit Part No. SB020266

Always use and follow planter manufacturers owner's manual recommended safety guidelines.

Prior to installation, unfold planter and leave the planter row units in the raised position.


See the attached Drawing No. SB020266, the AMVAC SmartBox System Parts and Operator's Manual and <u>www.amvacsmartbox.com</u> (About SmartBox, then Videos) website for additional installation information.

Note: The front mount bracket will mount using existing holes in the parallel arms closest to the row unit.




A. First, locate the four holes for mounting, and then remove the bolts mounting the down pressure springs (if equipped). Using the bushings and new hardware provided, re-attach the down pressure spring (if equipped) and the mounting bracket to the parallel arms, making sure to have the mounting brackets open section (top) facing forward toward the front of the planter. Tighten all four bolts so the bracket is secure to the row unit.





B. Install the SmartBox[®] cradle to the newly installed bracket. The two formed edges will slide under the rear side of the bracket. Use two bolts, washers and nuts provided in the row unit hardware to secure the cradle to the bracket. Tighten both bolts to secure.



C. The SmartBox[®] base container (with meter installed on base container) can now be installed.

Note: Meter attachment to the base container for the front mount will need to be secured at a 90° angle so the meter nipple delivering product faces the row it is feeding. See the meter installation instructions for proper installation.



	8	3	7	6	5	$\mathbf{\Phi}$	4	I	3	2	1 I	1	
			REVISION HISTORY			-				Parts L	ist		1
Ⅰ ⊢	REV	DATE	DESCRIPTION	BY ECO#				1	ITEM QTY PAR	T NO.	DESCRIPTIC	DN .	1
∣ ⊢			LEASE TO PROTO	JJA ⁻ JJA 7351				İ	1 1 SB020		ID CCS FM BRAC	KET. STD	-
b	A	2/24/11 RE	ELEASE TO PRODUCTION	JJA (351					*2 4 010512		SHING COLLAR,	· · · ·	D
								1	*3 8 FW-05		HER; 1/2 - 28 PE		-
)-250-5 BOLT; 1/2	,		-
					1 (\$9			-	*5 4 LN-050		; 1/2" NYLON INS		-
									\$6 1 SBCA0		ARTBOX BASE C		-
								-				UNI CRADLE	-
				Ĭ	\$7				\$7 4 FW-03	1 WASHER	FLAT, 5/16		L
								-	\$8 2 LN-031		; 5/16" NYLON IN		_
				•				l	\$9 2 BH-03	-150-5 BOLT; 5/16	6 X 1.50 GRADE 5)	_
			\$6	\$7									
				\$8					* = ITEMS IN	CLUDED IN PART	S BAG (BOLT KIT	, BOLT BAG	1
										NG BRACKET) PA			
q						+BOA				LUDED IN SMART	BOX ROW UNIT E	BASE	С
					ana!				CONTAIN	IER KIT			
₽													\mathbf{A}
				(1)									
					0	1							
					*3	B BB							
					$\square \lor$								
				0									
В					2 all	a al							В
						and //							
				~@			V						1
				Contraction of the second seco			-						1
				X		4	1		IT PARALLEL ARM				
				\sim '				BETWEE	N FLATWASHER AN	D FRAME MOUNT	(SB020269)		L
				(*5)		6							
											CONTAINED IN THIS DRAWING IS DRAWING MAY NOT BE USED	IS THE PROPERTY OF AMVA	
							\sim		TOLERANCES (EXCEPT AS NOTED	THE WRITTEN PERM	ISSION OF AMVAC CHEMICAL	CORP.	Ĩ
							:		(EXCEPT AS NOTED		AMVAC CH	IEMICAL	
					(*3)				2 PLACE DECIMALS	`.06	CORPOR		
					· (*2)				3 PLACE DECIMALS	` .030			
A					\smile \heartsuit				ANGLES		I TRAL FILL, FM BRKT		А
										DWG NO		REV	-
									DRAWN	size St	3020266	A	4
									ALL	B 1/11/2011 DATE S	CALE N/A SHEE	T1 OF 1	1
	8	3	7	6	5	4	4	I	3	2		1	
						•							